



# Christopher Peacock Paint

PRODUCT NAME: WALL EMULSION LOW LUSTRE

---

**Revision:** 12.06.07                      **Version:** 1.0.0  
**Print date:** 12.16.07

**01. Identification of substance, product and company**

**Product name:**

Wall Emulsion Low Lustre

**Use of the substance / product**

Wall Emulsion Low Lustre is a state-of-the-art, fast-drying, odorless acrylic paint suitable for use on properly primed sheetrock, plaster, wood, plastic and metal surfaces.

**Manufacturer / Supplier**

Christopher Peacock Paint

**Street / P.O. Box**

9 Bettswood Rd.

**Postal code / Town / City**

06851 / Norwalk

**Telephone / facsimile**

866.538.9260 / 203.987.4311

---

**02. Composition / information on ingredients**

This preparation does not contain any substances presenting a health or environmental hazard within the meaning of the Dangerous Substances Directive 67/548/EEC. This product does not contain any ingredients that are considered hazardous under the criteria of the OSHA Hazard Communication Standard (29 C.F.R. { 1910.1200.}).

**Hazardous components**

Not applicable.

---

**03. Hazards identification**

This preparation is not classified as dangerous according to the EC Directive 1999/45/EC. This product does not any ingredients that are considered hazardous under the criteria of the OSHA Hazard Communication Standard (29 C.F.R. { 1910.1200.}).

**Hazards designation according to 91/155/ECC**

Not applicable

---

**04. First-aid measures**

**General**

In case of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

**After inhalation**

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. Give nothing by mouth. If unconscious, place in recovery position and seek medical attention.

**After skin contact**





# Christopher Peacock Paint

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognized skin cleaner. Do NOT use solvents or thinners.

**After eye contact**

Remove contact lenses, irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical attention.

**After ingestion**

If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

---

**05. Fire-fighting measures**

**Suitable extinguishing media**

Alcohol resistant foam, CO<sub>2</sub>, powders, water spray

**Unsuitable extinguishing media**

Waterjet.

**Special risk posed by the substance or by the actual product, its combustion products or gases discharged**

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

**Special protective equipment**

Appropriate breathing apparatus may be required. For fighting fires in buildings and confined spaces, firefighters must use self-contained breathing apparatus and should wear full fire-fighting turn-out gear.

**Additional information**

Cool closed containers exposed to fire with water. Do not allow run-off from the fire fighting to enter drains of waterways.

---

**06. Accidental release measures**

**Personal precautions**

Eliminate sources of ignition and ventilate the area. Avoid breathing vapors. Refer to protective measures listed in sections 7 and 8.

**Environmental precautions**

Do not empty into drains. If the product is accidentally released into lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

**Methods for cleaning up/ collecting**

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent; avoid use of solvents.

---

**07. Handling and storage**

**Information for safe handling**

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentrations higher than the OEL (Occupational Exposure Limit). Additionally, the product should only be used in areas from which all naked lights and other sources of ignition have been eliminated. Electrical equipment should be protected to the appropriate standard. Floors should be of the conducting type. Product may charge electro statically: always ground containers when transferring from one container to another. Operators should wear antistatic footwear and clothing. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates and spray mist arising from the application of this product. Avoid inhalation of dust from sanding.

Smoking, eating and drinking should be prohibited in application area.

For personal protection see Section 8.

Never use pressure to empty: container is not a pressure vessel.

Always keep in containers of the same material as the original one.

Comply with the health and safety at work laws.

**Further information about storage conditions**





# Christopher Peacock Paint

Storage in accordance with CPR 15-1 or CPR 15-2. Observe label precautions. Store between 32 and 95 degrees F (0 and 35 degrees C) in a dry, well ventilated place away from sources of heat and direct sunlight.

Keep away from oxidizing agents, strongly alkaline and strongly acidic materials. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Do not allow to enter drains.

---

## 08. Exposure controls and personal protection

### Additional information about engineering measures

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

### Components with critical values that require monitoring at the workplace (exposure limits)

Not applicable

### Personal protective equipment

#### Hand protection

Solvent-resistant gloves may be appropriate gloves.

#### Eye protection

Safety glasses or goggles may be appropriate.

#### Body protection

Personnel should wear anti-static clothing made of natural fiber of high temperature resistant synthetic fiber.

---

## 09. Physical and chemical properties

### Relevant safety data

#### Physical state:

liquid  
Homogeneous viscous

#### Appearance:

liquid

**Boiling point / range:** (1013 hPa)

not applicable °C

**Boiling point hPa (Fahrenheit):** (1013 hPa)

not applicable °F

#### Flashpoint:

not applicable °C closed cup

#### Flashpoint [Fahrenheit]:

not applicable °F closed cup

**Specific gravity:** (20 °C / 68 °F)

1,02 – 1,06 G/CM<sup>3</sup>

**Solubility in water:** (20 °C / 68 °F)

thinnable % b.w.

**Flow time:** (20 °C / 68 °F)

90 s DIN-cup 4mm

**Viscosity KU:** (20 °C / 68 °F)

110-115 KU

---

## 10. Stability and reactivity

Stable under recommended storage and handling conditions (see section 7).

### Materials to avoid

Keep away from oxidizing agents, strongly alkaline and strongly acidic materials to avoid exothermic reactions.

### Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

---

## 11. Toxicological information

There are no data available on the product itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and not classified.

### Health effects from exposure:

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

The liquid splashed in the eyes may cause irritation and reversible damage.

---

## 12. Ecological information

There are no data on the product itself.





# Christopher Peacock Paint

The product should not be allowed to enter drains or waterways.

---

**13. Disposal considerations**

Do not empty into waters or drains.

---

**14. Transport information**

This preparation is not classified as dangerous according to the international transport regulations (ADR/RID, IMDG, ICAO.IATA)

**Land transport ADR / RID**

**Classification**

**Class:**

**Maritime transport IMDG / GGVSea**

**Classification**

**IMDG-Code:**

**Air transport ICAO-TI and IATA-DGR**

**Classification**

**Class:**

---

**15. Regulatory information**

**Classification according to EEC directives**

Not applicable

**International regulatory information**

U.S. Federal Regulations

Toxic Substances Control Act (TSCA) status: All ingredients are on the TSCA Inventory or excluded from TSCA.

This product does not contain any ingredients that are considered hazardous under the criteria of the OSHA Hazard Communication Standard (29 C.F.R. { 1910.1200.}).

State Regulations:

Contains ingredients listed under state right-to-know laws: New Jersey Worker Community Right to Know Act, Massachusetts Hazardous Substances Disclosure by Employers Act, Pennsylvania Worker and Community Right-to-Know Act, Michigan Natural Resources and Environmental Protection Act, Illinois Toxic Substances Disclosure to Employees Act, Minnesota Employee Right-to-Know Act.

---

**16. Other information**

**Further information**

The details in this material safety data sheet satisfy the U.S. Occupational Safety and Health Administration Hazard Communication Standard and legislation in the Netherlands and the European Union. The product is not to be used for other purposes than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps in order to fulfill the demand laid down in the local rules and legislation. The information in this SDS is meant as a description of the safety requirements of our product: it is not to be considered as a guarantee of the product's properties.

**Relevant changes**

02. Hazardous components 14. Land transport ADR/RID and GGVS/GGVE (2003) 14.

Classification (ADR) 14. Proper shipping name (ADR) 14. Maritime transport IMDG/GGVSea 14. Air transport ICAO-TI and IATA-DGR. 15. Special designation for certain preparations 15. OSHA HCS Class II Combustible liquid.

**Department issuing data sheet**

Chemtrec emergency hazardous information (Chemtrec@americanchemistry.com):

Domestic / North America: 800-424-9300

International: 703-527-3887 (call collect)

---

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

---

